

# Calibration Exciter VE-10

The VE-10 is a handy calibration exciter for a vibration meter and a vibration pickup (piezoelectric accelerometer).

- Calibrations of acceleration, velocity and displacement measurement equipment.
- 600 times of operation possible with single battery in auto-stop mode. Manual mode provided.
- Automatic power-off function for overload (more than 100 g).




Calibration of Vibration Level Meter Unit UV-15 by VE-10

## Specifications

Oscillator:	Sinusoidal wave oscillator
Frequency:	159.2 Hz ± 1 % for - 10 to + 55 °C
Acceleration:	10 m/s <sup>2</sup> (RMS) ± 3 % for 10 to 40 °C ± 5 % for - 10 to + 55 °C
Velocity:	10 m/s(RMS) ± 4 % for 10 to 40 °C ± 6 % for - 10 to + 55 °C
Displacement:	10 μm(RMS) ± 5 % for 10 to 40 °C ± 7 % for - 10 to + 55 °C
Maximum Load:	70 g
Transverse Amplitude:	Less than 5 % of main axis amplitude
Total Harmonic Distortion:	Less than 3 % for 20 to 60 g load Less than 5 % for 10 to 70 g load
Operation Mode:	Auto-stop mode (approx. one minute operation), Manual mode
Operating Conditions:	Temperature; -10 to + 55 °C Humidity; 0 to 90 % RH
Power:	IEC 6LR61 (9 V) battery × 1
Battery Life:	More than 600 operations for auto-stop mode More than 10 hours for continuous operation
Dimensions and Weight:	51 mm dia. × 134(H)mm, approx, 600 g(battery included)
Standard Accessories:	Mounting adapter × 1 M6 screw × 1 M6-UNF screw × 1 Leather case × 1 6LR61 alkaline battery × 1



RION Co., Ltd. is recognized by the JCSS which uses ISO/IEC 17025 (JIS Q 17025) as an accreditation standard and bases its accreditation scheme on ISO/IEC 17011. JCSS is operated by the accreditation body (IA Japan) which is a signatory to the Asia Pacific Laboratory Accreditation Cooperation (APLAC) as well as the International Laboratory Accreditation Cooperation (ILAC). The Quality & Environmental Management system Center of RION Co., Ltd. is an international MRA compliant JCSS operator with the accreditation number JCSS 0197.



ISO 14001 RION CO., LTD.  
ISO 9001 RION CO., LTD.

\* Specifications subject to change without notice.

Distributed by:

 **RION CO., LTD.**  
<http://rion-sv.com/>

3-20-41, Higashimotomachi, Kokubunji, Tokyo 185-8533, Japan  
Tel: +81-42-359-7888 Fax: +81-42-359-7442